


	CR 100A		CR 300A		CR 304S		CR 310A		CR 310XA		CR 320A	
	MM	IN	MM	IN	MM	IN	MM	IN	MM	IN	MM	IN
A	238,5	9,390	277,5	10,925	277,5	10,925	285	11,220	285	11,220	285	11,220
B	25	0,984	25	0,984	25	0,984	25	0,984	24	0,945	25	0,984
C	39,5	1,555	49,5	1,949	49,5	1,949	49,5	1,949	49,5	1,949	49,5	1,949
D	194	7,638	239	9,409	225	8,858	240	9,449	240	9,449	239	9,409
E	45	1,772	60	2,362	60	2,362	60	2,362	60	2,362	60	2,362
F	137	5,394	158	6,220	158	6,220	158	6,220	158	6,220	158	6,220
G	59	2,323	75	2,953	75	2,953	75	2,923	75	2,923	75	2,953
H	19	0,748	22,5	0,886	22,5	0,886	22,5	0,886	22,5	0,886	22,5	0,886
I	20	0,787	25	0,948	25	0,948	25	0,984	24	0,945	25	0,984
J	268,5	10,571	312,5	12,303	312,5	12,303	316	12,441	316	12,441	316	12,441

	CR 320XA		CR 400A		CR 404S		CR 410A		CR 410XA		CR 500A	
	MM	IN	MM	IN	MM	IN	MM	IN	MM	IN	MM	IN
A	285	11,220	301	11,850	301	11,850	317	12,480	317	12,480	311	12,244
B	24	0,945	25	0,984	25	0,984	25	0,984	25	0,984	30	1,181
C	49,5	1,949	59	2,323	59	2,323	59	2,323	59	2,323	69	2,717
D	239	9,409	237	9,331	240	9,449	258	10,157	258	10,157	266	10,472
E	60	2,362	73	2,874	73	2,874	73	2,874	73	2,874	73	2,874
F	158	6,220	172	6,772	172	6,772	172	6,772	172	6,772	184	7,244
G	75	2,953	84	3,307	84	3,307	84	3,307	84	3,307	91,5	3,602
H	22,5	0,886	28	1,102	28	1,102	28	1,102	28	1,102	32	1,260
I	24	0,945	30	1,181	30	1,181	30	1,181	30	1,181	30	1,181
J	316	12,441	341	13,425	341	13,425	347	13,661	347	13,661	351	13,819




CR 100A/300A/400A/500A




CAST HOSE GUARD

CR 310A/410A



SQUARE HEAD WITH PLATE HOSE GUARD

CR 320A




SQUARE HEAD WITH CAST HOSE GUARD

CR 304S/404S




STEEL HOSE GUARD

CR 310XA/410XA



SQUARE HEAD WITH 90° PIN HOLE AND PLATE HOSE GUARD

CR 320XA



SQUARE HEAD WITH 90° PIN HOLE AND CAST HOSE GUARD

	CR 100		CR 300		CR 400		CR 500	
	UNLIMITED	3625	UNLIMITED	3625	UNLIMITED	3625	UNLIMITED	3625
ROTATION ANGLE	UNLIMITED		UNLIMITED		UNLIMITED		UNLIMITED	
MAX PRESSURE (R) [BAR/PSI]	250	3625	250	3625	250	3625	250	3625
MAX PRESSURE (G) [BAR/PSI]	200	2900	200	2900	200	2900	200	2900
MAX PRESSURE (GC) [BAR/PSI]	300	4350	300	4350	300	4350	300	4350
DISPLACEMENT [CM <sup>3</sup> /IN <sup>3</sup> ]	139	8,5	330	20,1	420	25,6	465	28,4
TORQUE [NM/LB-FT]	450	332	900	664	1100	811	1400	1033
MAX AXIAL LOAD STAT [KN/LBF]	10	2248	30	6744	40	8992	55	12365
MAX AXIAL LOAD DYN [KN/LBF]	5	1124	15	3372	20	4496	25	5620
WEIGHT [KG/LB]	10	22	17	37,4	23	50,6	28	61,6
(310/410) [KG/LB]			16	35,2	22	48,4		
CONNECTIONS	G 1/4"	G 1/4"	G 3/8"	G 3/8"	G 3/8"	G 3/8"	G 3/8"	G 3/8"
REQ. OIL FLOW [LPM/GPM]	10	2,642	20	5,284	20	5,284	20	5,284



SELECT A CR A SERIES WHEN YOU NEED THE BEST PRODUCTIVITY AND POWER.

A LIGHT-WEIGHT AND EFFECTIVE HYDRAULIC ROTATORS WITH UNLIMITED ROTATION FOR ATV, AGRICULTURAL AND CARGO CRANES.

CHOOSE GENUINE FINN ROTOR ORIGINAL ACCESSORIES TO ENSURE SMOOTH WORKING. FROM THE WIDE VARIETY YOU WILL FIND ALL NECESSARY ACCESSORIES.

*get Your crane moving!*



*get Your crane moving!*

WWW.FINN-ROTOR.COM  
INFO@FINN-ROTOR.COM  
+358 14 417 8400

PL 96,43101 SAARIJÄRVI  
FINLAND